








Price List

Attn.: wanjun.w
 Tel: 0086-186-88384867
 Fax: 0086-020-26287877
 Company Name: Nomo Group CO.,Limited
 E-mail Address: sales@led321.com






Shipment Terms: EXW
 Payment Terms: T/T,Western Union
 Lead Time: 5 days after payment
 Quotation Date: 2013/1/2
 Valid Date: 30 days

LED Flood Light(Can be used in the solar system)

Item No.	Picture	LED	Description	Unit Price (MOQ20)	
				≥50pcs	Sample Price
F10A		10W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 10W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness: 950LM 7)Materials: Aluminum Alloy 8)Products Size:113*80*90mm 9)IP Grade : IP65 10)Beam Angle : 120*/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F10C		10W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 10W 3)Color Temperature: 2500-10000K 4)Ra > 78 5)Working Temperature: 50-35°C 6)Brightness: 950LM 7)Materials: Aluminum Alloy 8)Products Size:L145*W75*H50mm 9)IP Grade : IP65 10)Beam Angle : 120° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F20A		20W	1)Input Voltage:AC85-265V/12V/24V 2)Power: 20W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness: 90-100lm/W 7)Materials: Aluminum Alloy 8)Products Size:140*180*85mm 9)IP Grade : IP65 10)Beam Angle : 120*/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F30A		30W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 30W/40W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness: 90-100lm/W 7)Materials: Aluminum Alloy 8)Products Size:223*185*130mm 9)IP Grade : IP65 10)Beam Angle : 120*/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F40A		40W			
F30D		30W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 30W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness: 90-100lm/W 7)Materials: Aluminum Alloy 8)Products Size:223*185*130mm 9)IP Grade : IP65 10)Beam Angle : 90° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		

F30C		30W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 30W/40W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C		
F40C		40W	6)Brightness: 90-100lm/W 7)Materials: Aluminum Alloy 8)Products Size:L280*W220*H80mm 9)IP Grade : IP65 10)Beam Angle : 120° 12)Cover color : silver/black/ custom design		
F50D		50W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 50W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W 7)Materials: Aluminum Alloy 8)Products Size:285*235*150mm 9)IP Grade : IP65 10)Beam Angle : 90° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F50A		50W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 50W/60W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F60B		60W	7)Materials: Aluminum Alloy 8)Products Size:285*235*150mm 9)IP Grade : IP65 10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F50C		50W	1)Input Voltage: AC85-265V/12V/24V 2)Power: 50W/60W/70W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F60C		60W	7)Materials: Aluminum Alloy		
F70C		70W	8)Products Size:L350*W320*H105mm 9)IP Grade : IP65 10)Beam Angle : 120° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F60A		60W	1)Input Voltage: AC85-265V 2)Power: 60W/70W/80W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F70A		70W	7)Materials: Aluminum Alloy		
F80A		80W	8)Products Size: L392*W290*H114mm 9)IP Grade : IP65 10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F90A		90W	1)Input Voltage: AC85-265V 2)Power: 90W/100W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F100B		100W	7)Materials: Aluminum Alloy		
F110A		110W	8)Products Size: L392*W290*H114mm 9)IP Grade : IP67 10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		

F70B		70W	1)Input Voltage: AC85-265V 2)Power:70W/80W/90W/100W 3)Color Temperature: 2500-10000K		
F80B		80W	4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F90B		90W	7)Materials: Aluminum Alloy 8)Products Size:L393*W285*H93 9)IP Grade : IP65		
F100C		100W	10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F120B		120W	1)Input Voltage: AC85-265V 2)Power: 100W/120W/140W/160W 3)Color Temperature: 2500-10000K		
F140A		140W	4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F160B		160W	7)Materials: Aluminum Alloy 8)Products Size: L593*W285*H93mm 9)IP Grade : IP65		
F180A		180W	10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F150A		150W	1)Input Voltage: AC85-265V/no Frame 2)Power: 150W/180W/210W/240W 3)Color Temperature: 2500-10000K		
F180C		180W	4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100lm/W		
F210A		210W	7)Materials: Aluminum Alloy 8)Products Size: L593*W285*H93mm 9)IP Grade : IP65		
F240A		240W	10)Beam Angle : 120°/60° 12)Cover color : silver/black/ custom design		
F200A		200W	1)Input Voltage: AC85-265V/no Frame 2)Power: 200W/240W/280W/320W 3)Color Temperature: 2500-10000K		
F240B		240W	4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:90-100LM		
F280A		280W	7)Materials: Aluminum Alloy 8)Products Size: L960*W285*H93mm 9)IP Grade : IP65		
F320A		320W	10)Beam Angle : 120°/60° 11)Power Factor: > 0.98 12)Cover color : silver/black/ custom design		
F180B		180W	1)Input Voltage: AC85-265V/no Frame 2)Power: 180W 3)Color Temperature: 2500-10000K 4)Ra > 75 5)Working Temperature: 50-35°C 6)Brightness:100-110lm/W 7)Materials: Aluminum Alloy 8)Products Size: L450*W310*H210mm 9)IP Grade : IP65 10)Beam Angle : 120°/90° 12)Cover color : silver/black/ custom design		

PIR SENSOR LED floodlight					
F10B-PIR		10W	1)Detection distance:4~7M 2)Time-delay:5sec~10min 3)Detection range : 120°/60° 5)Input Voltage: AC85-265V/ DC12V /24V 6)Power: 10W 7)Color Temperature: 2500-10000K 8)Ra > 75 9)Working Temperature: 50-35°C 10)Brightness: 95LM/W 11)IP Grade : IP65 12)Beam Angle : 120°/60° 13)Power Factor: > 0.98		
F20A-PIR		20W	1)Detection distance:4~7M 2)Time-delay:5sec~10min 3)Detection range : 120°/60° 5)Input Voltage: AC85-265V/ DC12V /24V 6)Power: 20W 7)Color Temperature: 2500-10000K 8)Ra > 75 9)Working Temperature: 50-35°C 10)Brightness: 95LM/W 11)IP Grade : IP65 12)Beam Angle : 120°/60° 13)Power Factor: > 0.98		
F30A-PIR		30W	1)Detection distance:4~7M 2)Time-delay:5sec~10min 3)Detection range : 120°/60° 5)Input Voltage: AC85-265V/ DC12V /24V 6)Power: 30W 7)Color Temperature: 2500-10000K 8)Ra > 75 9)Working Temperature: 50-35°C 10)Brightness: 95LM/W 11)IP Grade : IP65 12)Beam Angle : 120°/60° 13)Power Factor: > 0.98		
F50A-PIR		50W	1)Detection distance:4~7M 2)Time-delay:5sec~10min 3)Detection range : 120°/60° 5)Input Voltage: AC85-265V/ DC12V /24V 6)Power: 50W 7)Color Temperature: 2500-10000K 8)Ra > 75 9)Working Temperature: 50-35°C 10)Brightness: 95LM/W 11)IP Grade : IP65 12)Beam Angle : 120°/60° 13)Power Factor: > 0.98		
RGB SENSOR LED floodlight					
F10WA-RGB		10W	1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 10W 3)Color Temperature: RGB 4)Working Temperature: 50-35°C 5)Materials: Aluminum Alloy 6)Products Size: 113*80*90mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%		

<p>F30WA-RGB</p>		<p>30W</p>	<p>1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 30W 3)Color Temperature: RGB 4)Working Temperature: 50-35°C 5)Materials: Aluminum Alloy 6)Products Size: 140*180*85mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%</p>		
<p>F50WA-RGB</p>		<p>50W</p>	<p>1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 50W 3)Color Temperature: RGB 4)Working Temperature: 50-35°C 5)Materials: Aluminum Alloy 6)Products Size: 285*235*150mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%</p>		
<p>Photo Sensor LED Floodlight</p>					
<p>F10WA-PS</p>		<p>20W</p>	<p>1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 20W 3)Electrical life: >6500 4)circles Turn on Lighting Level <25~35Lux 5)Turn off Lighting Level >150Lux 6)Products Size: 113*80*90mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%</p>		
<p>F30WA-PS</p>		<p>30W</p>	<p>1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 30W 3)Electrical life: >6500 4)circles Turn on Lighting Level <25~35Lux 5)Turn off Lighting Level >150Lux 6)Products Size: 113*80*90mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%</p>		
<p>F50WA-PS</p>		<p>50W</p>	<p>1)Input Voltage: AC85-265V/ DC12V /24V 2)Power: 50W 3)Electrical life: >6500 4)circles Turn on Lighting Level <25~35Lux 5)Turn off Lighting Level >150Lux 6)Products Size: 113*80*90mm 7)IP Grade : IP65 8)Beam Angle : 120°/60° 9)Power Factor: > 0.98 10)Power Efficiency : 82%</p>		

Note:

- 1:The price does not include taxes.
- 2:100% payment Before shipment.
- 3:The price is EPISTAR LED Chip;EDISON, BRIDGELUX are available.

PHOTOS

